

LISTING OF THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Previously Presented) A sprinkler comprising:
a rotatable nozzle housing having a water passage formed therein;
an output shaft mechanically connected to said rotatable nozzle housing for rotating said nozzle housing;
a manually adjustable rotatable sleeve having an inner surface and a plurality of circumferentially spaced nozzles; each of said nozzles having mutually different configurations from each other, said rotatable sleeve being slidably installed around the nozzle housing and being in rotational relationship therewith and thereto so that said rotatable sleeve can be selectively positioned to align one of said plurality of nozzles with the discharge end of the water passage for distributing water outwardly from said sprinkler; and

sealing means surrounding the discharge end of the water passage formed in said nozzle housing, said sealing means including a seal member surrounding the discharge end of the water passage and dimensioned to continuously bear against said inner surface of said rotatable sleeve to provide a sealed connection to the pressurized water passage of the nozzle housing; and means for retaining said rotatable sleeve in place.

2-3. Canceled

4. (Previously Presented) A sprinkler as claimed in claim 1, wherein said ~~seal~~ sealing means is an "O" ring.

5. (Previously Presented) A sprinkler as claimed in claim 1, wherein said rotatable nozzle housing is cylindrical and includes an outer surface, and said rotatable sleeve is dimensioned so that the outer diameter thereof is substantially equal to the outer diameter of said outer surface of said rotatable nozzle housing.

6. (Previously Presented) A sprinkler as claimed in claim 1, wherein a portion of said rotatable sleeve is blank, and wherein said rotatable sleeve can be selectively positioned so that said

blank portion overlies said discharge end of said water passage whereby said sprinkler is capable of being turned off without turning off the water supply.

7. (Previously Presented) A sprinkler as claimed in claim 6, wherein said rotatable nozzle housing includes a reduced diameter surface, said inner surface of said rotatable sleeve being in slidable relationship with said reduced diameter surface of said rotatable nozzle housing.

8. (Previously Presented) A sprinkler as claimed in claim 7, further comprising a riser assembly operatively connected to said rotatable nozzle housing, said riser assembly including a cylindrical member having an outer diameter, the outer diameter of said rotatable sleeve being substantially equal to the diameter of said outer diameter of said cylindrical member.

9. (Previously Presented) A sprinkler as set forth in claim 1, wherein said rotatable nozzle housing includes indicia on the top indicating the location of each orifice of said plurality of orifices and/or its flow characteristic.

10. (Previously Presented) A sprinkler as claimed in claim 1, wherein said rotatable sleeve is slidably installed from the top of said sprinkler.

11. (Previously Presented) A sprinkler as claimed in claim 1, wherein said nozzle housing further includes an outer surface, and
gripping means formed on said outer surface to hold said nozzle housing from rotating when said sleeve is rotated.

12. (Previously Presented) A sprinkler comprising:
a rotatable nozzle housing having ~~a water passage formed therein~~ and a central axis about which said rotatable nozzle housing rotates;
a relatively flat nozzle plate having a front side, a back side, a top edge, a bottom edge and opposing side edges;

at least one orifice disposed in said nozzle plate ~~to be aligned~~ aligning with the a water passage formed in said rotatable nozzle housing for discharging water from the side of said rotatable nozzle housing at a given characteristic,

said nozzle plate slidably fitting into a complementary groove formed ~~into said water passage~~ in said rotatable nozzle housing ~~so that~~ and disposed generally parallel to said central axis, said front side having a planar surface of said nozzle plate ~~can be sealed to the water passage by~~ facing the discharge end of said water passage,

sealing means surrounding said discharge end of said water passage formed in said nozzle housing; said sealing means including a seal member surrounding the discharge end of the water passage and dimensioned to continuously bear against said planar surface to provide a sealed connection to the pressurized water passage of the nozzle housing, wherein means on the top edge of said nozzle plate ~~[[is]]~~ accessible from the top of said rotatable nozzle housing ~~so as to be~~ wherein said nozzle plate is removable while said sprinkler is operational for insertion of ~~another~~ other nozzle plate ~~having at least one orifice and plates with different orifices~~ having different flow characteristics ~~from those of the removed nozzle plate.~~

13. (Previously Presented) A sprinkler as claimed in claim 12, wherein said seal member is an "O" ring.

14. (Previously Presented) A sprinkler as claimed in claim 12, including a tapered recess formed at one end of said groove and a mating tapered portion formed on said ~~nozzle plate~~ bottom edge and said back side to urge said nozzle plate against said seal member.

15. (Previously Presented) A sprinkler as claimed in claim 12, including a riser operatively connected to said rotatable nozzle housing, said riser and said nozzle housing being cylindrically shaped and the outer diameter of said riser and the outer diameter of said nozzle housing being substantially equal.

16. (Previously Presented) A water sprinkler comprising:
a riser assembly;
a drive shaft extending from the top of said riser assembly;

a nozzle housing assembly having
a housing connected to said drive shaft for rotation therewith,
a cylindrical outer surface, and
a flow passage formed therein which has an exit at said cylindrical outer surface; and
a cylindrical nozzle selection sleeve mounted over the outer surface of said housing to rotate therewith and being manually rotatable relative to said housing, said nozzle selection sleeve having a sleeve wall with a multiplicity of individual nozzles spaced therearound, said individual nozzles having mutually different configurations from each other to produce respectively different flow characteristics and being positioned on said sleeve wall so that each nozzle becomes aligned with said flow passage exit as the nozzle selection sleeve is rotated.

17. (Previously Presented) A water sprinkler as claimed in claim 16, wherein each of said individual nozzles includes a sharp edged orifice formed therein in the process of molding the nozzle selection sleeve.

18. (Previously Presented) A water sprinkler as claimed in claim 16, further including a seal surrounding said flow passage exit to provide a sealed connection between the nozzle housing and the selection sleeve around the pressurized [water] flow passage of the nozzle housing to prevent water exiting the flow passage and through the nozzle aligned with the flow passage exit from leaking.

19. (Previously Presented) A water sprinkler as claimed in claim 18, wherein said seal includes an "O" ring.

20. (Previously Presented) A sprinkler as claimed in claim 1, wherein the rotatable sleeve is removably installed on the nozzle housing.

21. (Previously Presented) A water sprinkler as claimed in claim 16, wherein the nozzle selection sleeve is slidably removable from said housing.

22. (Previously Presented) A sprinkler comprising:

a riser assembly;
a rotatable nozzle housing having a flow passage formed therein for discharging water
therefrom;
a drive shaft extending from the riser assembly and connected to the nozzle housing for
rotating the nozzle housing relative to the riser assembly; and
at least one selectable nozzle arrangement for aligning one of a plurality of nozzle orifices
with the flow passage to distribute water from the sprinkler according to desired flow
characteristics, wherein the plurality of nozzle orifices are each configured mutually differently to
provide different flow characteristics, and wherein a selected one of the plurality of nozzle orifices
to be aligned with the flow passage can be changed while the sprinkler is operational.

23. (Previously Presented) The sprinkler according to claim 22, wherein the at least one
selectable nozzle arrangement includes at least one nozzle plate each having at least one orifice
disposed therein.

24. (Previously Presented) The sprinkler according to claim 23, wherein the nozzle
housing has a groove formed therein, whereby a nozzle plate can be slidably fitted into the groove
and accessed from the top of the nozzle housing so as to be mountable in the nozzle housing while
the sprinkler is operational and similarly removable therefrom for insertion of another nozzle plate
having another of the plurality of differently configured nozzle orifices.

25. (Previously Presented) The sprinkler according to claim 23, wherein each nozzle
plate is mountable in the nozzle housing so as to intersect the flow passage to align the selected one
of the differently configured nozzle orifices with the flow passage, whereby a pressurized flow of
water flowing through the flow passage is forced through the selected nozzle orifice to achieve the
desired flow characteristics.

26. (Previously Presented) The sprinkler according to claim 23, wherein the at least one
nozzle plate includes a nozzle plate having an insertable nozzle inserted into the plate.

27. (Previously Presented) The sprinkler according to claim 22, wherein the at least

one selectable nozzle arrangement includes a nozzle sleeve mountable around and dismountable from the rotatable nozzle housing, the nozzle sleeve being rotatable relative to the rotatable nozzle housing and having the plurality of nozzle orifices formed therein.

28. (Previously Presented) The sprinkler according to claim 22, wherein the selectable nozzle arrangement is removable from the sprinkler housing while the sprinkler is operational so as to be exchangeable.

29-31. Canceled

32. (Previously Presented) The sprinkler as claimed in claim 1, including nozzle means in said manually adjustable rotatable sleeve.